



High Street



120
Carine



300
Cottesloe



520
Scarborough



545
Subiaco



550
Trigg



730
Cervantes

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice.
*Subject to proper installation, maintenance and local building code/regulatory approval.

High Street

Inspired by the stunning landscapes of Western Australia, High Street combines the beautiful look of natural timber with the astonishing durability and impact resistance of hybrid technology.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.3mm	Surface	Embossed
Wear Layer	0.3mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 180mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm EVA
M ² per Box	1.62m ²	Profile	Micro Bevel
M ² per Pallet	113.40m ²	Protective Coating	PUR & Scratch Resistance
Colours	6		
Installation Method	Uniclic® (Angle-Angle)		

Performance

Impact Sound Reduction	Test Application	Ln'T,w	Result
	150mm Slab + 28mm Furrings + 10mm Plasterboard	52	
	200m Slab	56	ISO140-7 /
	200mm Slab + 28mm Furrings + 10mm Plasterboard	51	ISO717.2
	200mm Slab + R2.5 Insulation + 100mm Cavity + 10mm Plasterboard	48	
	250mm Slab + 28mm Furrings + 10mm Plasterboard	50	
Fire Classification	CRF 11.0kW/m ² , Smoke Value 530% minutes	EN ISO 9239-1	
Slip Resistance	P3	AS 4586	
Residential Warranty*	Lifetime Structural Limited Residential Warranty 15 Year Hybrid Limited Residential Warranty		
Commercial Warranty†	3 Year Commercial Warranty available upon request		

Sustainability

Indoor Air Quality	Green Building Council compliant for VOC emission rate limits
Global GreenTag	GreenRate Level A certified



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after five years. For full information in respect to the scope and limitations of this warranty, please refer to the to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.