



F L O O R S

PRODUCT SPECIFICATION

HIGH STREET HYBRID

Product Detail

Type	Hybrid
Plank Thickness	6.3mm
Wear Layer	0.3mm
Dimensions	1500mm (L) x 180mm (W)
Planks per Box	6
M ² per Box	1.62m ²
M ² per Pallet	113.4m ²
Colours	8
Finish	Matte
Surface	PUR, Scratch Resistant, Embossed
Profile	Micro Bevel
Top Layer	Decorative Film & Wear Layer
Substrate Layer	Trigon® Core Technology (Limestone Composite)
Backing layer	1.5mm EVA
Installation Methods	Angle / Angle

Performance

Slip Resistance	P3	AS/NZ 4586
Fire Classification	CRF 11.0kW/m ² , Smoke Value 530% minutes	EN ISO 9239-1
VOC	CETEC Compliant for VOC Emission Rate Limits	
Impact Sound Reduction	TBC - waiting on test results	ISO 10140-3 ASTM E492-09

Warranty

Residential	15 years*
Commercial	3 years†

*These residential warranties are in addition to any rights consumers may have under Australian consumer laws. Conditions apply: For full information in respect to the scope and limitations of these warranties, this must be read in conjunction with the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com.

†Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst Floors commercial account manager.

Colour Summary

Colour Number	Colour Name
110	APPLE CROSS
170	BURSWOOD
300	COTTESLOE
520	SCARBOROUGH
540	COOGEE
545	SUBIACO
555	MT LAWLEY
730	CERVANTES