



# Apollo Hardwood



105  
**Blackbutt**  
Ivory



505  
**Blackbutt**  
Limed



525  
**Blackbutt**  
Sandbank



535  
**Blackbutt**  
Elegant



545  
**Blackbutt**  
Classic



735  
**Blackbutt**  
Stormy



520  
**Spotted Gum**  
Blonde



530  
**Spotted Gum**  
Coastal



540  
**Spotted Gum**  
Riverbank



555  
**Spotted Gum**  
Natural



710  
**Spotted Gum**  
Ash



790  
**Spotted Gum**  
Burnt

While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference. Actual samples should be inspected at your nearest retailer to confirm texture and colour before making a purchase decision. \*Subject to proper installation and maintenance.

# Apollo Hardwood

Comprising of homegrown wood species Blackbutt and Spotted Gum in a stunning longboard, Apollo Hardwood promises a distinctly Australian look. Each design is represented in six distinct shades to complement your unique interior style. With the astonishing durability and waterproof properties of Godfrey Hirst hybrid flooring, Apollo Hardwood is ideal for all areas of a busy home.

## Technical Data

<b>Type</b>	Hybrid	<b>Finish</b>	Matte
<b>Plank Thickness</b>	6.5mm	<b>Surface</b>	Embossed
<b>Wear Layer</b>	0.5mm	<b>Top Layer</b>	Decorative Film & Wear Layer
<b>Dimensions</b>	1830mm (L) x 152mm (W)	<b>Substrate Layer</b>	Trigon® Core Technology (Limestone Composite)
<b>Planks per Box</b>	6	<b>Backing Layer</b>	1.5mm EVA
<b>M<sup>2</sup> per Box</b>	1.67m <sup>2</sup>	<b>Profile</b>	Micro Bevel
<b>M<sup>2</sup> per Pallet</b>	110.22m <sup>2</sup>	<b>Protective Coating</b>	PUR
<b>Colours</b>	12		
<b>Installation Method</b>	Unipush™ Tap fold-down		

## Performance

<b>Dimensional Stability</b>	Length: 0.05% Width: -0.00% Curling: 0.00%	ISO23999
<b>Thermal Resistance</b>	0.056m <sup>2</sup> .K/w	EN 12667
<b>Thermal Conductivity</b>	0.115 W/(m.K)	EN 12667
<b>Abrasion Rating</b>	Group T	EN 660-2
<b>Swelling After Submersion in Water</b>	0.3%	ISO 24336
<b>Impact Sound Reduction</b>	Ln,W 52 & IIC 58	ISO 10140-3, ASTM E492-09
<b>Light Fastness</b>	Grade 6	EN ISO 105-B02
<b>Fire Classification</b>	CRF 10.9kW/m <sup>2</sup> Smoke Value 81% minutes	ISO 9239
<b>Slip Resistance</b>	P3	AS/NZ 4586 - 2013
<b>Residential Warranty*</b>	25 years	
<b>Commercial Warranty†</b>	15 years	

## Sustainability

**Indoor Air Quality** Green Building Council compliant for VOC emission rate limits



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst hybrid floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. \*These residential warranties are in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under these warranties. Conditions apply: Warranties apply to residential indoor use of the floor installed and maintained in accordance with Godfrey Hirst's guidelines. The amount recoverable under the warranties decreases after five years. For full information in respect to the scope and limitations of these warranties, refer to the Godfrey Hirst Hybrid Floors Care, Maintenance and Warranties guide (which also includes full information as to the installation, care and characteristics of Godfrey Hirst hybrid products) available from your retailer, by calling 1300 444 778, or by download from [www.godfreyhirst.com](http://www.godfreyhirst.com) †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.