



Metropol 1500



100
Alabaster



180
Burnt Umber



300
Sable Oak



500
Cornsilk



520
Brass Oak



545
Apple-Box Gum



555
Marble Spotted Gum



560
Burl Oak



580
Fallow Oak



700
Platinum Grey



720
Pepper Oak



790
Silhouette Oak

While all care is taken, product images may vary in colour due to possible printing process variations. Images are to be used as a guide only to give an idea of the colour and nuances of the pattern, but are not fully representative of the variations among the planks (which reflects the natural product which inspired the design). For a representative view of the surface structure and variations within the design, take a look at the big samples on display and ask your retailer for more advice. *Subject to proper installation, maintenance and local building code/regulatory approval.

Metropol 1500

Delivering super durable and impact resistant flooring with exquisite design, Metropol 1500 is a technologically advanced hybrid range that ticks all the right boxes. Available in a wide range of natural timber hues, your next project is a guaranteed winner with strong, stable and beautiful flooring that's easy to install.

Technical Data

Type	Hybrid	Finish	Matte
Plank Thickness	6.5mm	Surface	Embossed
Wear Layer	0.5mm	Top Layer	Decorative Film & Wear Layer
Dimensions	1500mm (L) x 228mm (W)	Substrate Layer	Trigon® Core Technology (Limestone Composite)
Planks per Box	6	Backing Layer	1.5mm IXPE
M² per Box	2.05m ²	Profile	Micro Bevel
M² per Pallet	123.12m ²	Protective Coating	PUR
Colours	12		
Installation Method	Uniclic®		

Performance

Dimensional Stability	Length: 0.0 Width: 0.0 Curling 0.0	ISO23999	
Thermal Resistance	0.039m ² K/w	ISO 8301	
Thermal Conductivity	0.128 W/(m.K)	ISO 8301	
Abrasion Rating	Group T	EN 660-2	
Swelling After Submersion in Water	0.1%	ISO 24336	
Light Fastness	≥6	EN ISO 105-B02	
Light Reflectance Values	100 Alabaster 46.14 % 500 Cornsilk 30.04% 555 Marble Spotted Gum 12.32% 700 Platinum Grey 33.98%	180 Burnt Umber 8.60% 520 Brass Oak 22.30% 560 Burl Oak 11.41% 720 Pepper Oak 19.10%	300 Sable Oak 18.44% 545 Apple-Box Gum 20.90% 580 Fallow Oak 15.47% 790 Silhouette Oak 13.31%
Fire Classification	CRF 11.1kW/m ² Smoke Value 210% minutes	ISO 9239	
Slip Resistance	P3	AS/NZ 4586 - 2013	
Residential Warranty*	25 Year Hybrid Limited Residential Warranty		
Commercial Warranty†	10 Year Commercial Warranty available upon request		

Sustainability

Indoor Air Quality Green Building Council compliant for VOC emission rate limits



Manufactured under a quality and environmental system certified as complying with ISO9001 and 14001. Test results and certificates are available on request. Specifications and colourations are subject to manufacturing tolerances. As part of Godfrey Hirst's continuous improvement process, Godfrey Hirst reserves the right to change the specifications of or delete colours of this product without notice. All Godfrey Hirst Hybrid Floors must be installed in accordance with relevant Australian Standards and in conjunction with the Godfrey Hirst Hybrid Floors Installation Instructions. *This product comes with a residential warranty for new product installed indoors in a residential home, if properly installed and maintained. This warranty is in addition to consumers' rights under the statutory consumer guarantee provisions in the Australian Consumer Law, which may exceed the rights under this warranty. The amount recoverable under the warranty decreases after fifteen years. For full information in respect to the scope and limitations of this warranty, please refer to the full terms and conditions available from your retailer, by calling 1300 444 778, or by download from www.godfreyhirst.com. †Terms and conditions apply to all commercial warranties – contact your Godfrey Hirst account manager.