

Specification Data Sheet

ORIGIANL 8mm & 12mm Laminate Click flooring for floating install only.

ORIGIANL collection is an authentic look laminate flooring presented with stunning European Oak & Australian Timber visuals. The décors offer cool washed out and muted tones along with classic Australian Timber colours. The palette displays all the warmth and character normally associated more expensive natural timber flooring. With two versatile thicknesses ORIGIANL 8 & 12mm laminate delivers great value for money without compromising quality or appeal.

ORIGIANL laminate is dimensionally stable, exceptionally durable and delivers great visual appeal for residential décors, and multi-residential apartments.

Key Features; Engineered to exacting standards. Manufactured from sustainable wood fibre forest resources. Extremely stable with excellent wear resistance, AC4 (12mm) & AC3 (8mm).

Colour Range; 14 Colour decors for 12mm & 8 Colour decors for 8 mm, including Blackbutt & Spotted Gum.

Description; Laminate with a patented click profile for floating installation.

Grade & Surface; 12mm-AC4 & 8mm -AC3 surface for high scratch resistant performance. Matte coating, registered embossed surface.

Size & Length; 12mm – 2200 x 193mm Quantity; 1.698m² / carton. 8mm - 1215 x 195mm Quantity; 1.895m² / carton

Profile; Unilin Angle to Angle Click profile. Micro Bevelled Edges.

Acoustic outcome; Test Result with 2mm Green Underlay, 12mm - L'nT,w 45 & 8mm - L'nT,w 44.

Fire Test Data; AS/ISO9239.1-2003, 12mm CHF, 6.1kW/m² & MSD, 6% minutes. 8mm CHF, 5.4kW/m² & MSD, 9% minutes.

Slip Resistance; In accordance with AS/NZS 4586; 2013 P1. VOC Emissions; E1, (Below World Health Organisation Levels).

R-Value Thermal Resistance EN 12996:2001; 12mm - 0.0730 & 8mm - 0.0520

Accessories; Alloy trims, MDF coloured scotia & Stair Nosing available to support colour selection for interior fit-out.

Pre-finished, quick, and easy to lay - no dust, no smell, and no mess. Please consult with your supplier for specific site install guidelines prior to installation. For specification or reseller support contact, info@preferencefloors.com.au or a local sales office.

www.preferencefloors.com.au

Adelaide (SA)

t +61 8 8262 2774
sa@preferencefloors.com.au

Brisbane (QLD)

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne (VIC)

t +61 3 9794 5111
vic@preferencefloors.com.au

Perth (WA)

t +61 8 9471 7785
wa@preferencefloors.com.au

Sydney (NSW)

t +61 2 9738 1188
sales@preferencefloors.com.au